



Clean. Modern. Precise.
Double and triple pane glass in a thermally broken aluminum frame.
The A5 delivers energy savings, durability, and value.



ALUMINUM DOUBLE + TRIPLE PANE





A5 DOUBLE PANE



A5 TRIPLE PANE

A5 Double Pane Performance

- Thermal performance R-3.2-R-3.57 hr-ft²-F/BTU
- Uw- 0.28-0.31, Uf- 0.28, Ug-0.18, BTU/hr.-ft².-F
- Psi-Spacer-0.032 BTU/hr.-ft.-F
- Solar heat gain coefficient between 0.28-.60

A5 Triple Pane Performance

- Thermal performance R-5 hr-ft²-F/BTU
- Uw-0.20, Uf-0.28, Ug-0.10, BTU/hr.-ft².-F
- Psi-Spacer-0.032 BTU/hr.-ft.-F
- Solar heat gain coefficient between 0.28-.60


All aluminum frames with continuous insulation provide excellent durability and quality. Our hardware ensures smooth operation and impeccable style. The A5 provides modern performance and sleek architectural lines that are ideal for modern projects.

Aligned frame thickness between fixed and operable windows. Available as fixed windows, tilt-turn windows, french windows, inward opening awning windows, tilt-only windows, and swing doors, french doors, lift & slide doors and postless corner doors.

WINDOW & DOOR STYLES




Tilt-Turn Window




French Window



Fixed Window



Inward Opening Awning




Tilt-only Window



Swing Door



Lift & Slide Door*



Postless Corner Door*

*multiple panel options

Min./Max. Dimensions:

Operable window sizes: up to 25 sqft.

Fixed window sizes: up to 80 sqft.

Swing door sizes: up to 4'x9'-10" (per panel)

Lift&Slide door sizes: 10'x up to 32'
and 8'x up to 40' (8'-0" maximum panel width)



FRAME COLOR OPTIONS | 300+ powder-coated color options available

